

## Web Sensor CO2 mätare för ventilationskanal med Ethernet - kopia

Art nr: T6545



Web Sensor CO2-transmitter med sond för montage i ventilationskanal och nätverksanslutning - Ethernet.

Web Sensor för CO2 med sond för montage i ventilationskanal.

CO<sub>2</sub>-mätaren är byggd runt en tvåstråles NDIR-sensor med dubbla våglängder som automatiskt kompenserar för sensorns åldrande. Sensorn är motståndskraftig mot nedsmutsning och erbjuder underhållsfri mätning och utmärkt långtidsstabilitet. Unik autokalibrering som eliminerar behovet av periodisk kalibrering i fält.

**Possibility to [extend the measuring range](#) for an additional charge:**

- Measuring range: 0 to 10 000 ppm
- Accuracy: 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

### Tekniska specifikationer

TEMPERATURE SENSOR	
Measuring range	-30 to +60 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	± 2,5 % RH
Resolution	0.1% RH
DEW POINT	
Measuring range	-60 to +80 °C
Accuracy	±1.6°C at ambient temperature T<25°C and RH>30%
Resolution	0.1 °C
CO2 SENSOR	
Measuring range	0 to 2000 ppm
Accuracy	±(50ppm +2% from reading) at 25°C and 1013hPa
Resolution	1 ppm
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C

Channels	internal CO <sub>2</sub> sensor
Output	Ethernet
Measuring interval	15 s
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	9-30 Vdc
Protection class	IP30 electronics; IP20 sesors
Dimensions	89 x 73 x 240 mm; stem length 130 mm
Weight	approx. 260 g
Warranty	3 years